

Forklift Seat Belt

Seat Belt for Forklift - Described in the Regulation guidelines are the use of seatbelts and operator restraints on lift trucks. It states that the accountability falls on the employers' to make sure that every machine, piece of equipment and tool is utilized rightly used in accordance to the directions of the maker.

Rough Terrain lift trucks should meet the regulations of ANSI Standard ASME B56.6-1992 in regards to their use, design, maintenance, inspection and fabrication.

Side boom tractors and mobile machine along with a Rollover Protective Structure, or ROPS for short, should contain seat belts which meet the requirements of the Society of Automotive Engineers, or SAE, Standard J386 JUN93, Operator Restraint System for Off-Road Work Machines. If whatever mobile equipment has seat belts required by law, the driver and subsequent passengers need to make certain they utilize the belts whenever the motor vehicle is in motion or engaged in operation for the reason that this could cause the equipment to become unsteady and thus, not safe.

If a seat belt or different operator restraint is required on a forklift.

The seat belt requirements while working a lift truck depend on various factors. Whether or not the lift truck is equipped along with a Rollover Protective Structure, the type of lift truck itself and the year the forklift was manufactured all contribute to this determination. The manufacturer's instructions and the requirements of the applicable standard are referenced in the Regulation.

With regards to to a driver restraint device, enclosure or system, ANSI Standard ASME B56.1-1993 in the case of powered industrial trucks, is intended to be able to assist the driver in reducing the probability of entrapment of the torso and/or head between the truck and the ground in the event of a tip over. The restraint device or system could consist of a seat belt, even though a seat belt is not necessarily a part of such machine or system.